



**PRODUCT TECHNICAL DATA SHEET**

Revised: APRIL 2022

<b>Catalogue Reference:</b>	<b>AN15/55R BA with Smooth Textured Insert</b>	
<b>Uniclass2015:</b>	<b>Pr_35_90_31_74 RIGID STAIR NOSINGS</b>	
<b>General Description:</b>	<p><b>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL</b>  <b>Single Channel/Raked Front. Supplied with Smooth Textured PVC Infill.</b></p> <p>Infill colour options:            Black, Light Grey, Porth Stone, Polar Grey.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;">             Smooth Textured Infill SRVs: PTV Dry - 65 PTV Wet - 56           </div>	
		
<b>Specifications:</b>	Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound
	Tread Dimension	66mm
	Nosing Dimension	55mm
	Gauge	3.5mm ramping down to 0.5mm
	Lengths available	Cut to customer sizes up to 2500mm
	Finishes available	Black Anodised.
	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads.  Drilled for size 8 screws. Fixings not supplied.
<b>Application:</b>	To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Installation guide available.	
<b>Suitability:</b>	For stairs with low to medium foot traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.	
<b>Additional Information:</b>	Also available with AT149.5 tread insert for an all-aluminium installation.	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

**Manufacturers Of The Finest Specialist Flooring Accessories**  
**www.thecatweb.com**