




Part of the COBA Group

PRODUCT TECHNICAL DATA SHEET

Revised: February 2023

Catalogue Reference:	AN51 DC	
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS	
General Description:	<p>DESIGNER COLLECTION ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL Single Channel/Square Front. Supplied with Smooth Textured PVC Infill.</p> <p>Infill colour options: Black, Light Grey, Porth Stone, Polar Grey.</p> 	
	<div style="border: 1px solid black; padding: 5px; width: fit-content;"> Smooth Textured Infill SRVs: PTV Dry - 65 PTV Wet - 56 </div>	
Specifications:	Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound
	Tread Dimension	62mm
	Nosing Dimension	32mm
	Gauge	5mm
	Lengths available	Cut to customer sizes up to 2750mm
	Finishes available	Bronze, Light Bronze DESIGNER  COLLECTION
	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads. Drilled for size 8 screws. Fixings not supplied.
Application:	For abutting to carpet and carpet tiles to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Compatible with profiles ANE Nap Detail, ANRE25 Ramp Detail and ANEXT extension tread. Installation guide available.	
Suitability:	Medium to heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public building, as well as for quality domestic installations.	
Additional Information:	Also available with AT149.5 tread insert for an all-aluminium installation and PVC Castellated infill for interior installation.	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com