



# PRODUCT TECHNICAL DATA SHEET


Revised: APRIL 2022

**Catalogue Reference:** AN15/55 BA with Smooth Textured Insert

**Uniclass2015:** Pr\_35\_90\_31\_74 RIGID STAIR NOSINGS

**General Description:** **ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL**  
Single Channel/Square Front. Supplied with Smooth Textured PVC Infill.

Infill colour options:  
Black, Light Grey, Porth Stone, Polar Grey.



Smooth Textured Infill SRVs: PTV Dry - 65 PTV Wet - 56

**Specifications:**

Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound
Tread Dimension	66mm
Nosing Dimension	55mm
Gauge	3.5mm ramping down to 0.5mm
Lengths available	Cut to customer sizes up to 3200mm
Finishes available	Black Anodised
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads.  Drilled for size 8 screws. Fixings not supplied.

**Application:**

To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino.  
Installation guide available.

**Suitability:**

For stairs with low to medium foot traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.

**Additional Information:**

Also available with AT149.5 tread insert for an all-aluminium installation.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

**Manufacturers Of The Finest Specialist Flooring Accessories**  
**www.thecatweb.com**