

PRODUCT TECHNICAL DATA SHEET

AN51/55 DC

Uniclass2015:

Pr_35_90_31_74 RIGID STAIR NOSINGS

General Description:

Catalogue Reference:

DESIGNER COLLECTION ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL


Single Channel/Square Front. Supplied with Castellated PVC Infill.

Infill colour options:

Black, White, Light Grey, Flint, Granite, Rustic, Fawn, Ivory, Spruce, Jade, Regency, Mid Blue, Nimbus, Peat, Yellow, Poppy, Claret,

Porth Stone, Polar Grey.

Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76



Revised: February 2023

Specifications:

Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound
Tread Dimension	62mm
Nosing Dimension	55mm
Gauge	5mm
Lengths available	Cut to customer sizes up to 2750mm
Finishes available	Bronze, Light Bronze DESIGNER COLLECTION
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads. Drilled for size 8 screws. Fixings not supplied.

Application:

For abutting to carpet and carpet tiles to finish the nose edge of stairs.

Can be rebated to sit flush in wooden steps.

Compatible with profiles ANE Nap Detail, ANRE25 Ramp Detail and

ANEXT extension tread. Installation guide available.

Suitability:

Medium to heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public building, as well as for quality domestic installations.

Additional Information:

Also available with ATI49.5 tread insert for an all-aluminium installation and Smooth Texture PVC infill for interior application.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com