

## PRODUCT TECHNICAL DATA SHEET

Catalogue Reference:

AN15R DC

Uniclass2015:

Pr\_35\_90\_31\_74 RIGID STAIR NOSINGS

**General Description:** 

DESIGNER COLLECTION ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL


Single Channel/Raked Front. Supplied with Castellated PVC Infill.

Infill colour options:

Black, White, Light Grey, Flint, Granite, Rustic, Fawn, Ivory, Spruce, Jade, Regency, Mid Blue, Nimbus,

Peat, Yellow, Poppy, Claret, Porth Stone, Polar Grey.

Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76



Revised: February 2023

**Specifications:** 

Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound
Tread Dimension	63.5mm
Nosing Dimension	30mm
Gauge	4mm ramping down to 0.5mm
Lengths available	Cut to customer sizes up to 2500mm
Finishes available	Bronze, Light Bronze  DESIGNER  COLLECTION
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads.  Drilled for size 6 screws.  Fixings not supplied.

**Application:** 

To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Installation guide available.

Suitability:

Medium to heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public building, as well as for quality domestic installations.

Additional Information:

Also available with ATI49.5 tread insert for an all-aluminium installation and Smooth Textured PVC infill for interior installation.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories www.thecatweb.com