



Part of the COBA Group

PRODUCT TECHNICAL DATA SHEET

Revised: February 2023

Catalogue Reference:

AN15 DC

Uniclass2015:

Pr_35_90_31_74 RIGID STAIR NOSINGS

General Description:


DESIGNER COLLECTION ALUMINIUM STAIR NOSING WITH SLIP RESISTANT TREAD INSERT

Single Channel/Square Front. Supplied with ATI49.5 Tread Insert.

Tread Insert Finishes:
Bronze, Light Bronze.

Finishes can be supplied to match or to contrast with the base profile, as preferred.

DESIGNER
COLLECTION



Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76

Specifications:

Material	Aluminium Alloy 6063 T6
Tread Dimension	63.5mm
Nosing Dimension	30mm
Gauge	4mm ramping down to 0.5mm
Lengths available	Cut to customer sizes up to 2750mm
Finishes available	Bronze, Light Bronze
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the tread insert to cover the screw heads. Drilled for size 6 screws. Fixings not supplied.

Application:

To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino.
Installation guide available.

Suitability:

Medium to heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public building, as well as for quality domestic installations.

Additional Information:

Also available with Castellated/Smooth Textured PVC Infill for interior applications.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com