

PRODUCT TECHNICAL DATA SHEET

| , | | |
|--|--|---|
| Catalogue Reference: | AN61 DC | |
| Uniclass2015: | Pr_35_90_31_74 RIGID STAIR NOSINGS | |
| General Description: | DESIGNER COLLECTION ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL Single Channel/Raked Front. Supplied with Smooth Textured PVC Infill. | |
| | Infill colour options: Black, Light Grey, Porth Stone, Polar Grey. | 5 [5] 32 |
| | Smooth Textured Infill SRVs: PTV Dry - 65 PTV Wet - 56 | |
| Specifications: | Materials | Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound |
| | Tread Dimension | 62mm |
| | Nosing Dimension | 32mm |
| | Gauge | 5mm |
| | Lengths available | Cut to customer sizes up to 2750mm |
| | Finishes available | Bronze, Light Bronze DESIGNER COLLECTION |
| | Drilling | Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads. Drilled for size 8 screws. Fixings not supplied. |
| Application: | For abutting to carpet and carpet tiles to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Compatible with profiles ANE Nap Detail, ANRE25 Ramp Detail and ANEXT extension tread. Installation guide available. | |
| Suitability: | Medium to heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public building, as well as for quality domestic installations. | |
| Additional Information: | Also available with ATI49.5 Tread Insert for an all-aluminium installation and Smooth Textured PVC infill for interior installation. | |
| Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres. | | |

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories www.thecatweb.com