





PRODUCT TECHNICAL DATA SHEET

Revised: January 2018

Catalogue Reference:	KSP5 – KLIKS SPECTRUM ZIP TWIN TOP	
Uniclass2015:	Pr_35_90_31_90 TWO PART FLOOR TRANSITION STRIPS	
General Description:	PROFILE FOR JOINING FLOOR COVERINGS OF THE SAME HEIGHT.	
	<p>Serrated down legs to interlock with KB4 base profiles.</p> 	
	 <p>This profile contains up to 33% Recycled Factory Stream Waste</p>	
Specifications:	Material	Co-Extruded PVC Compound
	Visible surface when installed	38mm
	Height adjustment	5mm to 23mm, depending on chosen base
	Compatible bases	KB1, KB2, KB3, KAB38, KAB60.
	Lengths available	2715mm
	Colours available	Black, Granite, Peat, Grey
	Standard supply	Undrilled.
Application:	<p>Installed in combination with chosen base to protect the edges of the floor coverings. The base is firmly affixed to the substrate floor then KSP5 top pressed down over it to engage interlock feature between the two profiles. Can be formed to curves on site to a minimum radius of 1500mm when installed with either KB1, KB2 or KB3 bases. For use with timber, laminates, ceramic, stone, carpet and carpet tiles.</p>	
Suitability:	<p>Medium to heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public building, as well as for quality domestic installations.</p>	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com