



PRODUCT TECHNICAL DATA SHEET

Issued: October 2021

Catalogue Reference:

AN15

Uniclass2015:


Pr_35_90_31_74 RIGID STAIR NOSINGS

General Description:

ALUMINIUM STAIR NOSING WITH SLIP RESISTANT TREAD INSERT
Single Channel/Square Front. Supplied with ATI49.5 Tread Insert.

Tread Insert Finishes & LRV's:

Mill Aluminium	Avg. LRV 71.65
Polished Aluminium	Avg. LRV 75.55
Satin Aluminium	Avg. LRV 65.40
Black Anodised	Avg. LRV 4.80



Finishes can be supplied to match or to contrast with the base profile, as preferred.

Castellated ATI Infill SRVs: PTV Dry - 82 PTV Wet - 54

Specifications:

Material	Aluminium Alloy 6063 T6
Tread Dimension	63.5mm
Nosing Dimension	30mm
Gauge	4mm ramping down to 0.5mm
Lengths available	Cut to customer sizes up to 3200mm
Finishes available & LRV's	Mill Aluminium Avg. LRV 71.65 Polished Aluminium Avg. LRV 75.55 Satin Aluminium Avg. LRV 65.40
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the tread insert to cover the screw heads. Drilled for size 8 screws. Fixings not supplied.

Application:

To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino.
Installation guide available.

Suitability:

Very heavy interior foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Additional Information:

Also available with Olympic Grip carborundum infill for exterior/wet applications and Castellated/Smooth Textured PVC Infill for interior applications.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com