




PRODUCT TECHNICAL DATA SHEET

Revised: October 2021

Catalogue Reference:	AN52R	
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS	
General Description:	<p>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT INFILL Double Channel/Raked Front. Supplied with Olympic Grip Infill.</p> <p>Infill Colour Options & LRV's: Olympic Black LRV: 4.85</p> 	
	<p>Olympic Grip Infill SRVs: PTV Dry - 92 PTV Wet - 86</p>	
Specifications:	Material	Aluminium Alloy 6063 T6
	Tread Dimension	90mm
	Nosing Dimension	32mm
	Gauge	5mm
	Lengths available	Cut to customer sizes up to 2500mm
	Finishes available & LRV's	Mill Aluminium Avg. LRV 71.65 Polished Aluminium Avg. LRV 75.55 Satin Aluminium Avg. LRV 65.40
	Drilling	<p>Can be supplied undrilled or pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill.</p> <p>Drilled for size 8 screws. Fixings not supplied.</p>
Application:	<p>For abutting to carpet and carpet tiles to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Compatible with profiles ANE Nap Detail, ANRE25 Ramp Detail and ANEXT extension tread. Installation guide available.</p>	
Suitability:	<p>Heavy foot traffic and exterior/wet situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.</p>	
Additional Information:	<p>Also available with ATI37.25 tread insert for an all-aluminium installation, and Castellated/Smooth Textured PVC infill for interior applications.</p>	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com