



PRODUCT TECHNICAL DATA SHEET

Revised: October 2021

Catalogue Reference:

ATI 62

Uniclass2015:


Pr_35_90_31_84 STAIR TRIMS

General Description:

ALUMINIUM STAIR INSERT WITH SLIP RESISTANT INFILL Single Channel. Supplied with Castellated PVC Infill as standard (Smooth Textured infill on request)

Infill Colour Options & LRV's:

Black LRV:4.25, **White** LRV:84.22, **Light Grey** LRV:12.33, **Flint** LRV:11.27, **Granite** LRV:7.02, **Rustic** LRV:5.52, **Fawn** LRV:11.27, **Ivory** LRV:37.42, **Spruce** LRV:6.38, **Jade** LRV:7.33, **Regency** LRV:5.16, **Mid Blue** LRV:6.53, **Nimbus** LRV:4.77, **Peat** LRV:5.88, **Yellow** LRV:54.91, **Poppy** LRV:10.01, **Claret** LRV:5.83, **Porth Stone** LRV:52.91, **Polar Grey** LRV:42.53



Castellated SRVs: PTV Dry - 85 PTV Wet - 76

Specifications:

Material	Aluminium Alloy 6063 T6
Tread Dimension	62mm
Nosing Dimension	n/a
Gauge	5mm
Lengths available	Cut to customer sizes up to 2750mm
Finishes available	Mill Aluminium Avg. LRV 71.65
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads. Drilled for size 8 screws. Fixings not supplied.

Application:

For rebating into stone and wooden steps or with ceramic tiles, to provide a visual aid and some slip resistance.
Installation guide available.

Suitability:

Very heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com