



PRODUCT TECHNICAL DATA SHEET

Issued: October 2021

Catalogue Reference:

ATI 62

Uniclass2015:


Pr_35_90_31_84 STAIR TRIMS

General Description:

**ALUMINIUM STAIR INSERT WITH SLIP RESISTANT INFILL
Single Channel. Supplied with ATI49.5 Tread Insert**

Tread Insert Finishes & LRV's:

Mill Aluminium	Avg. LRV 71.65
Polished Aluminium	Avg. LRV 75.55
Satin Aluminium	Avg. LRV 65.40
Black Anodised	Avg. LRV 4.80



Castellated SRVs: PTV Dry - 82 PTV Wet - 54

Specifications:

Material	Aluminium Alloy 6063 T6
Tread Dimension	62mm
Nosing Dimension	n/a
Gauge	5mm
Lengths available	Cut to customer sizes up to 2750mm
Finishes available	Mill Aluminium Avg. LRV 71.65
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the tread insert to cover the screw heads. Drilled for size 8 screws. Fixings not supplied.

Application:

For rebating into stone and wooden steps or with ceramic tiles, to provide a visual aid and some slip resistance.
Installation guide available.

Suitability:

Very heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com