



PRODUCT TECHNICAL DATA SHEET

Revised: October 2021

Catalogue Reference:	AN70/30 RCF	
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS	
General Description:	<p>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT CASTELLATED TREAD Single Channel/Raked Front. Supplied with ATI12.5 Tread Insert.</p> <p>ATI 12.75 concealing strip finishes: Mill Aluminium Avg. LRV 71.65 Polished Aluminium Avg. LRV 75.55 Satin Aluminium Avg. LRV 65.40 Finishes can be supplied to match or to contrast with the base profile, as preferred.</p> <div style="text-align: right;"> </div> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> Castellated Tread SRVs: PTV Dry - 82 PTV Wet - 54 </div>	
Specifications:	Material	Aluminium Alloy 6063 T6
	Tread Dimension	69mm
	Nosing Dimension	30mm
	Gauge	4.5mm ramping down to 0.5mm
	Lengths available	Cut to customer sizes up to 2500mm
	Finishes available & LRV's	Mill Aluminium Avg. LRV 71.65 Polished Aluminium Avg. LRV 75.55 Satin Aluminium Avg. LRV 65.40
	Drilling	<p>Can be supplied pre-drilled and countersunk in the rear channel for concealed fixing and on-site retro fitting of cover strip.</p> <p>Drilled for size 8 screws. Fixings not supplied.</p>
Application:	<p>To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Installation guide available.</p>	
Suitability:	<p>Heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.</p>	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com