




PRODUCT TECHNICAL DATA SHEET

Revised: June 2019

| | | | | | | | | | | | | | | | | |
|--------------------------------|---|--|----------|-------------------------|--------------------------------|------|-------------------|---|------------------|---------------|-------------------|--------|--------------------|--------------------|-----------------|------------|
| Catalogue Reference: | KK123 - KLIKS RAMP TOP ALUMINIUM | | | | | | | | | | | | | | | |
| Uniclass2015: | Pr_35_90_31_90 TWO PART FLOOR TRANSITION STRIPS | | | | | | | | | | | | | | | |
| General Description: | PROFILE FOR JOINING FLOOR COVERINGS OF DIFFERENT HEIGHTS. Serrated down leg to interlock with KB base profiles. Allows up to 12mm expansion. | | | | | | | | | | | | | | | |
| |  | | | | | | | | | | | | | | | |
| Specifications: | <table border="1"><tr><td>Material</td><td>Aluminium Alloy 6063 T6</td></tr><tr><td>Visible surface when installed</td><td>55mm</td></tr><tr><td>Height adjustment</td><td>9.5mm to 23mm, depending on chosen base</td></tr><tr><td>Compatible bases</td><td>KB1, KB2, KB3</td></tr><tr><td>Lengths available</td><td>2715mm</td></tr><tr><td>Finishes available</td><td>Polished Aluminium</td></tr><tr><td>Standard supply</td><td>Undrilled.</td></tr></table> | | Material | Aluminium Alloy 6063 T6 | Visible surface when installed | 55mm | Height adjustment | 9.5mm to 23mm, depending on chosen base | Compatible bases | KB1, KB2, KB3 | Lengths available | 2715mm | Finishes available | Polished Aluminium | Standard supply | Undrilled. |
| Material | Aluminium Alloy 6063 T6 | | | | | | | | | | | | | | | |
| Visible surface when installed | 55mm | | | | | | | | | | | | | | | |
| Height adjustment | 9.5mm to 23mm, depending on chosen base | | | | | | | | | | | | | | | |
| Compatible bases | KB1, KB2, KB3 | | | | | | | | | | | | | | | |
| Lengths available | 2715mm | | | | | | | | | | | | | | | |
| Finishes available | Polished Aluminium | | | | | | | | | | | | | | | |
| Standard supply | Undrilled. | | | | | | | | | | | | | | | |
| Application: | Installed in combination with one of three compatible bases to protect the edges of the floor coverings. The chosen KB base is firmly affixed to the substrate floor then the top pressed down over it to engage interlock feature between the two profiles. Ideal for finishing timber, ceramic tiles, laminates and any other flooring that requires expansion. | | | | | | | | | | | | | | | |
| Suitability: | Heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public building, as well as for quality domestic installations. | | | | | | | | | | | | | | | |

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com