




PRODUCT TECHNICAL DATA SHEET

Revised: Oct 2021

Catalogue Reference:	BTI 49.5									
Uniclass2015:	Pr_35_90_31_84 STAIR TRIMS									
General Description:	<p>BRASS STAIR INSERT WITH CASTELLATED TREAD</p> <p>Finishes & LRV's:</p> <table border="0"> <tr> <td>Polished Brass</td> <td>Avg. LRV 71.45</td> </tr> <tr> <td>Satin Brass</td> <td>Avg. LRV 59.55</td> </tr> <tr> <td>Antique Brass</td> <td>Avg. LRV 29.55</td> </tr> <tr> <td>Antique Bronze</td> <td>Avg. LRV 9.15</td> </tr> </table> <div style="text-align: right;">  </div> <div style="border: 1px solid black; padding: 5px; margin-top: 10px; text-align: right;"> <p>SRVs: PTV Dry - 73 PTV Wet - 45</p> </div>		Polished Brass	Avg. LRV 71.45	Satin Brass	Avg. LRV 59.55	Antique Brass	Avg. LRV 29.55	Antique Bronze	Avg. LRV 9.15
Polished Brass	Avg. LRV 71.45									
Satin Brass	Avg. LRV 59.55									
Antique Brass	Avg. LRV 29.55									
Antique Bronze	Avg. LRV 9.15									
Specifications:	Material	Solid Brass Grade H/H CZ108 BS EN 12164:2016								
	Tread Dimension	49.5mm								
	Nosing Dimension	n/a								
	Gauge	2.3mm								
	Lengths available	Cut to customer sizes up to 2750mm								
	Finishes available	Polished Brass, Satin Brass, Antique Brass, Antique Bronze. Antique Brass and Antique Bronze finishes are a chemically applied process and are hand finished with a variance from batch to batch. They are not foot-traffic resistant and are designed to create an aged, unpolished effect.								
	Drilling	Supplied undrilled for *adhesive fixing. Can be supplied drilled for size 8 screws. Fixings not supplied. When supplied as a stair nosing insert plate, fixing is by Stick Fix tape pre-applied to the underside. *We recommend Stycco Flex rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use.								
Application:	For rebating into stone and wooden steps or between ceramic tiles, to provide a visual aid and some slip resistance. Can be supplied as a tread insert with C.A.T. brass profiles with equivalent infill pocket dimensions for an all-brass installation where concealed fixings are required. Installation guide available.									
Suitability:	Heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.									

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com