



## PRODUCT TECHNICAL DATA SHEET

Issued: October 2021

**Catalogue Reference:** AN15R BA

**Uniclass2015:** Pr\_35\_90\_31\_74 RIGID STAIR NOSINGS

**General Description:**


**ALUMINIUM STAIR NOSING WITH SLIP RESISTANT TREAD INSERT**  
**Single Channel/Raked Front. Supplied with ATI49.5 Tread Insert.**

Tread Insert Finishes & LRV's:

Mill Aluminium Avg. LRV 71.65  
Polished Aluminium Avg. LRV 75.55  
Satin Aluminium Avg. LRV 65.40  
Black Anodised Avg. LRV 4.80

Finishes can be supplied to match or to contrast with the base profile, as preferred.

Castellated Infill SRVs: PTV Dry - 82 PTV Wet - 54



**Specifications:**

Material	Aluminium Alloy 6063 T6
Tread Dimension	63.5mm
Nosing Dimension	30mm
Gauge	4mm ramping down to 0.5mm
Lengths available	Cut to customer sizes up to 2500mm
Finish & LRV	Black Anodised Avg. LRV 4.80
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the tread insert to cover the screw heads.  Drilled for size 8 screws. Fixings not supplied.

**Application:**

To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino.  
Installation guide available.

**Suitability:**

For stairs with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.

**Additional Information:**

Also available with Olympic Grip carborundum infill for exterior/wet applications and Castellated/Smooth Textured PVC Infill for interior applications.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

**Manufacturers Of The Finest Specialist Flooring Accessories**  
**www.thecatweb.com**