




PRODUCT TECHNICAL DATA SHEET

Revised: Oct 2021

Catalogue Reference:	AN81 BA	
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS	
General Description:	<p>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL Single Channel/Round Front. Supplied with Castellated PVC Infill</p> <p>Infill Colour Options & LRV's: Black LRV:4.25, White LRV:84.22, Light Grey LRV:12.33, Flint LRV:11.27, Granite LRV:7.02, Rustic LRV:5.52, Fawn LRV:11.27, Ivory LRV:37.42, Spruce LRV:6.38, Jade LRV:7.33, Regency LRV:5.16, Mid Blue LRV:6.53, Nimbus LRV:4.77, Peat LRV:5.88, Yellow LRV:54.91, Poppy LRV:10.01, Claret LRV:5.83, Porth Stone LRV:52.91, Polar Grey LRV:42.53</p> 	
	Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76	
Specifications:	Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound
	Tread Dimension	68mm
	Nosing Dimension	40mm
	Gauge	5mm
	Lengths available	Cut to customer sizes up to 2700mm
	Finish & LRV	Black Anodised Avg. 4.80
	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill. Drilled for size 8 screws. Fixings not supplied.
Application:	For abutting to carpet and carpet tiles to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Installation guide available.	
Suitability:	For stair with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.	
Additional Information:	Also available with AT149.5 tread insert for an all-aluminium installation and Olympic Grip carborundum infill for exterior/wet applications.	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com