




## PRODUCT TECHNICAL DATA SHEET

Revised: Oct 2021

<b>Catalogue Reference:</b>	<b>AN15/55/13</b>									
<b>Uniclass2015:</b>	<b>Pr_35_90_31_74 RIGID STAIR NOSINGS</b>									
<b>General Description:</b>	<p><b>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL &amp; RISER HIGHLIGHT STRIP</b>  <b>Single Channel/Square Front. Supplied with Smooth Textured PVC Infill.</b></p> <p>Tread Insert Finishes &amp; LRV's:</p> <table> <tr> <td>Black</td> <td>LRV 4.47</td> </tr> <tr> <td>Light Grey</td> <td>LRV 12.74</td> </tr> <tr> <td>Porth Stone</td> <td>LRV 53.11</td> </tr> <tr> <td>Polar Grey</td> <td>LRV 42.73</td> </tr> </table> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;">           Smooth Textured Infill SRVs: PTV Dry - 65 PTV Wet - 56         </div> 		Black	LRV 4.47	Light Grey	LRV 12.74	Porth Stone	LRV 53.11	Polar Grey	LRV 42.73
Black	LRV 4.47									
Light Grey	LRV 12.74									
Porth Stone	LRV 53.11									
Polar Grey	LRV 42.73									
<b>Specifications:</b>	Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound								
	Tread Dimension	66.3mm								
	Nosing Dimension	55mm								
	Gauge	4.25mm ramping down to 0.5mm								
	Lengths available	Cut to customer sizes up to 3200mm								
	Finishes & LRV's	<b>Mill Aluminium</b> Avg. LRV 71.65 <b>Polished Aluminium</b> Avg. LRV 75.55 <b>Satin Aluminium</b> Avg. LRV 65.40								
	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads.  Drilled for size 8 screws. Fixings not supplied.								
<b>Application:</b>	To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Installation guide available.									
<b>Suitability:</b>	Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.									
<b>Additional Information:</b>	Also available with ATI49.5 tread insert for an all-aluminium installation and Olympic Grip carborundum infill for exterior/wet applications.									

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

**Manufacturers Of The Finest Specialist Flooring Accessories**  
**www.thecatweb.com**