



PRODUCT TECHNICAL DATA SHEET

Issued: June 2019

Catalogue Reference:	KKSL24ES13 - KLIKS SLIM ALUMINIUM END STOP WITH EXP15 FLEXIBLE PVC/NITRILE EXPANSION FEATURE	
Uniclass2015:	Pr_35_90_31_90 TWO PART FLOOR TRANSITION STRIPS	
General Description:	<p>PROFILE FOR FINISHING THE EDGE OF FLOOR COVERINGS.</p> <p>Serrated down leg to interlock with KKS B base profiles. Allows up to 10mm of movement. EXP15 expansion medium will deform by 10mm and recover.</p>	
Specifications:	Materials	Aluminium Profile: Aluminium Alloy 6063 T6 Expansion Medium: Flexible PVC/Nitrile to BSS86/Shore hardness A57, opaque with colour additive.
	Visible surface when installed	40mm overall
	Height adjustment	8mm to 20mm, depending on chosen base
	Compatible bases	KKSBA1, KKSBA2, KKSBP9.5, KKSBP12, KKSBP15, KKSBP20.
	Lengths available	2715mm
	Aluminium finish	Satin Aluminium
	Standard supply	Undrilled.
Application:	<p>Installed in combination with one of six compatible bases to protect the edges of the floor coverings. The chosen KKS B base is firmly affixed to the substrate floor then the top pressed down over it to engage interlock feature between the two profiles. Ideal for finishing timber, ceramic tiles, laminates and any other flooring that requires expansion.</p>	
Suitability:	<p>Medium to heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public building, as well as for quality domestic installations.</p>	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com