




## PRODUCT TECHNICAL DATA SHEET

Revised: October 2021

<b>Catalogue Reference:</b>	<b>ANT60/55/12.5</b>	
<b>Uniclass2015:</b>	<b>Pr_35_90_31_74 RIGID STAIR NOSINGS</b>	
<b>General Description:</b>	<p><b>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT INFILL</b>  <b>Single Channel/Square Front. Supplied with Olympic Grip carborundum Infill.</b></p> <p>Infill Colour Options &amp; LRV's:  <b>Olympic Black</b> LRV: 4.85</p> <div style="text-align: right;">  </div>	
	<p>Olympic Grip Infill SRVs: PTV Dry - 92 PTV Wet - 86</p>	
<b>Specifications:</b>	Material	Aluminium Alloy 6063 T6
	Tread Dimension	60mm
	Nosing Dimension	55mm
	Gauge	12.5mm
	Lengths available	Cut to customer sizes up to 2750mm
	Finishes available & LRV's	<b>Mill Aluminium</b> Avg. LRV 71.65 <b>Satin Aluminium</b> Avg. LRV 65.40
	Drilling	Can be supplied pre-drilled and countersunk in the rear tail plate. Fixings are concealed by the adjoining floor covering.  Drilled for size 8 screws. Fixings not supplied.
<b>Application:</b>	For use with thicker floor coverings such as ceramics, stone and timber to finish the nose edge of stairs. Installation guide available.	
<b>Suitability:</b>	Heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

**Manufacturers Of The Finest Specialist Flooring Accessories**  
**www.thecatweb.com**