



PRODUCT TECHNICAL DATA SHEET

Revised: Oct 2021

Catalogue Reference:	AN15 BA															
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS															
General Description:	<p>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL Single Channel/Square Front. Supplied with Smooth Textured PVC Infill.</p> <p>Tread Insert Finishes & LRV's:</p> <table> <tr> <td>Black</td> <td>LRV 4.47</td> </tr> <tr> <td>Light Grey</td> <td>LRV 12.74</td> </tr> <tr> <td>Porth Stone</td> <td>LRV 53.11</td> </tr> <tr> <td>Polar Grey</td> <td>LRV 42.73</td> </tr> </table> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;"> Smooth Textured Infill SRVs: PTV Dry - 65 PTV Wet - 56 </div>		Black	LRV 4.47	Light Grey	LRV 12.74	Porth Stone	LRV 53.11	Polar Grey	LRV 42.73						
Black	LRV 4.47															
Light Grey	LRV 12.74															
Porth Stone	LRV 53.11															
Polar Grey	LRV 42.73															
Specifications:	<table border="1"> <tr> <td>Materials</td> <td>Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound</td> </tr> <tr> <td>Tread Dimension</td> <td>63.5mm</td> </tr> <tr> <td>Nosing Dimension</td> <td>30mm</td> </tr> <tr> <td>Gauge</td> <td>4mm ramping down to 0.5mm</td> </tr> <tr> <td>Lengths available</td> <td>Cut to customer sizes up to 2700mm</td> </tr> <tr> <td>Finish & LRV</td> <td>Black Anodised Avg. LRV 4.80</td> </tr> <tr> <td>Drilling</td> <td>Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill. Drilled for size 8 screws. Fixings not supplied.</td> </tr> </table>	Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound	Tread Dimension	63.5mm	Nosing Dimension	30mm	Gauge	4mm ramping down to 0.5mm	Lengths available	Cut to customer sizes up to 2700mm	Finish & LRV	Black Anodised Avg. LRV 4.80	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill. Drilled for size 8 screws. Fixings not supplied.	
Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound															
Tread Dimension	63.5mm															
Nosing Dimension	30mm															
Gauge	4mm ramping down to 0.5mm															
Lengths available	Cut to customer sizes up to 2700mm															
Finish & LRV	Black Anodised Avg. LRV 4.80															
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill. Drilled for size 8 screws. Fixings not supplied.															
Application:	To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Installation guide available.															
Suitability:	For stairs with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.															
Additional Information:	Also available with ATI49.5 tread insert for an all-aluminium installation and Olympic Grip carborundum infill for exterior/wet applications.															

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com