



PRODUCT TECHNICAL DATA SHEET

Revised: Oct 2021

Catalogue Reference:	BN59R/SL									
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS									
General Description:	<p>BRASS STAIR NOSING WITH SLIP RESISTANT OLYMPIC GRIP INFILL Single Channel/Raked Front. Supplied with Olympic Grip carborundum Infill.</p> <p>Infill Colour Options & LRV's:</p> <p>Olympic Black LRV: 4.85</p> <div style="text-align: right;"> </div> <div style="border: 1px solid black; padding: 5px; margin-top: 10px; width: fit-content; margin-left: auto;"> <p>Olympic Grip Infill SRVs: PTV Dry - 92 PTV Wet - 86</p> </div>									
Specifications:	Material	Solid Brass Grade H/H CZ108 BS EN 12164:2016								
	Tread Dimension	59mm								
	Nosing Dimension	30mm								
	Gauge	2.5mm								
	Lengths available	Cut to customer sizes up to 2500mm								
	Channel Finishes available & Associated Light Reflective Values or LRV's	<table border="0"> <tr> <td>Polished Brass</td> <td>Avg. LRV 71.45</td> </tr> <tr> <td>Satin Brass</td> <td>Avg. LRV 59.55</td> </tr> <tr> <td>Antique Brass</td> <td>Avg. LRV 29.55</td> </tr> <tr> <td>Antique Bronze</td> <td>Avg. LRV 9.15</td> </tr> </table> <p>Antique Brass and Antique Bronze finishes are a chemically applied process and are hand finished with a variance from batch to batch. They are not foot-traffic resistant and are designed to create an aged, unpolished effect.</p>	Polished Brass	Avg. LRV 71.45	Satin Brass	Avg. LRV 59.55	Antique Brass	Avg. LRV 29.55	Antique Bronze	Avg. LRV 9.15
Polished Brass	Avg. LRV 71.45									
Satin Brass	Avg. LRV 59.55									
Antique Brass	Avg. LRV 29.55									
Antique Bronze	Avg. LRV 9.15									
	Drilling	Can be supplied undrilled or pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill. Drilled for size 6 screws. Fixings not supplied.								
Application:	To butt to laminates, LVT, vinyl, lino.									
Suitability:	Heavy foot traffic such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.									
Additional Information:	Also available with Castellated/Smooth Textured PVC infill and BTI49.5 tread insert for an all-brass installation.									

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com