




PRODUCT TECHNICAL DATA SHEET

Revised October 2021

Catalogue Reference:	BTI 60															
Uniclass2015:	Pr_35_90_31_84 STAIR TRIMS															
General Description:	<p>BRASS STAIR INSERT WITH SLIP RESISTANT INFILL Single Channel. Supplied with Castellated PVC Infill (Smooth Textured infill on request)</p> <p>Infill Colour Options & LRV's: Black LRV:4.25, White LRV:84.22, Light Grey LRV:12.33, Flint LRV:11.27, Granite LRV:7.02, Rustic LRV:5.52, Fawn LRV:11.27, Ivory LRV:37.42, Spruce LRV:6.38, Jade LRV:7.33, Regency LRV:5.16, Mid Blue LRV:6.53, Nimbus LRV:4.77, Peat LRV:5.88, Yellow LRV:54.91, Poppy LRV:10.01, Claret LRV:5.83, Porth Stone LRV:52.91, Polar Grey LRV:42.53</p> <div style="border: 1px solid black; padding: 2px; width: fit-content; margin: 10px auto;"> Castellated SRVs: PTV Dry - 85 PTV Wet - 76 </div>															
Specifications:	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Material</td> <td>Solid Brass Grade H/H CZ108 BS EN 12164:2016</td> </tr> <tr> <td>Tread Dimension</td> <td>60mm</td> </tr> <tr> <td>Nosing Dimension</td> <td>n/a</td> </tr> <tr> <td>Gauge</td> <td>5mm</td> </tr> <tr> <td>Lengths available</td> <td>Cut to customer sizes up to 2750mm</td> </tr> <tr> <td>Finishes available & LRV's</td> <td>Matt Brass Avg LRV 60.55</td> </tr> <tr> <td>Drilling</td> <td> Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads. Drilled for size 8 screws. Fixings not supplied. </td> </tr> </table>		Material	Solid Brass Grade H/H CZ108 BS EN 12164:2016	Tread Dimension	60mm	Nosing Dimension	n/a	Gauge	5mm	Lengths available	Cut to customer sizes up to 2750mm	Finishes available & LRV's	Matt Brass Avg LRV 60.55	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads. Drilled for size 8 screws. Fixings not supplied.
Material	Solid Brass Grade H/H CZ108 BS EN 12164:2016															
Tread Dimension	60mm															
Nosing Dimension	n/a															
Gauge	5mm															
Lengths available	Cut to customer sizes up to 2750mm															
Finishes available & LRV's	Matt Brass Avg LRV 60.55															
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads. Drilled for size 8 screws. Fixings not supplied.															
Application:	For rebating into stone and wooden steps or with ceramic tiles, to provide a visual aid and some slip resistance. Installation guide available.															
Suitability:	Very heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.															



Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com