



PRODUCT TECHNICAL DATA SHEET

Revised: Oct 2021

Catalogue Reference:

BTI 60

Uniclass2015:


Pr_35_90_31_84 STAIR TRIMS

General Description:

BRASS STAIR INSERT WITH SLIP RESISTANT INFILL
Single Channel. Supplied with BTI49.5 Tread Insert

Finishes & LRV's:

| | |
|----------------|----------------|
| Polished Brass | Avg. LRV 71.45 |
| Satin Brass | Avg. LRV 59.55 |
| Antique Brass | Avg. LRV 29.55 |
| Antique Bronze | Avg. LRV 9.15 |



Finishes can be supplied to match or to contrast with the base profile, as preferred.

Castellated SRVs: PTV Dry - 82 PTV Wet - 54

| | |
|---------------------|---|
| Material | Solid Brass Grade H/H CZ108 BS EN 12164:2016 |
| Tread Dimension | 60mm |
| Nosing Dimension | n/a |
| Gauge | 5mm |
| Lengths available | Cut to customer sizes up to 2750mm |
| Finishes available | Polished Brass, Satin Brass, Antique Brass, Antique Bronze. Antique Brass and Antique Bronze finishes are a chemically applied process and are hand finished with a variance from batch to batch. They are not foot-traffic resistant and are designed to create an aged, unpolished effect. |
| Drilling | Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the tread insert. Drilled for size 8 screws. Fixings not supplied. |
| Application: | For rebating into stone and wooden steps or with ceramic tiles, to provide a visual aid and some slip resistance. Installation guide available. |
| Suitability: | Very heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings. |

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com