



PRODUCT TECHNICAL DATA SHEET

Revised: October 2021

Catalogue Reference:


BRASS STUDS

Uniclass2015:

Pr_35_90_60_22 DEMARCATION INSERTS

General Description:

BRASS DEMARCATION STUDS – PLAIN SURFACE PATTERN To provide a demarcation boundary line, e.g., outside seating areas between coffee houses and step edges. The low profile design does not present a trip hazard and will not confuse people with impaired vision. Larger diameter studs can be used on Roadways to demarcate parking bays, etc.



Finishes & LRV's

Mill Brass Avg. LRV 60.55
Antique Brass Avg. LRV 29.55

Specifications:

Material	Solid Brass Grade H/H CZ121 BS EN 12164:2016
Top Diameter	25mm
Top Height	3mm
Locating Leg Dims	20mm long x 10mm diameter
Pack Quantity	Details on request
Finishes available	Mill Brass, Antique Bronze. Antique Bronze finish is a chemically applied process and is hand finished with a variance from batch to batch. It is not foot-traffic resistant and is designed to create an aged, unpolished effect.
Fixing	Adhesive. We recommend Stycco Flex rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use.

Application:

Demarcation studs are designed to be retro fitted once the paving has been installed.
Installation is by drilling holes at the desired spacings, typically 300mm centres.

Suitability:

Medium to heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com