

ALUMINIUM STAIR NOSING WITH SLIP RESISTANT CASTELLATED TREAD
 Single Channel/Raked Front. Supplied with ATI12.5 Tread Insert.



PRODUCT TECHNICAL DATA SHEET

Revised: October 2021

Catalogue Reference:	AN70/55 RCF	
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS	
General Description:	<p>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT CASTELLATED TREAD Single Channel/Raked Front/Ramped Back . Supplied with Smooth PVC Tread Insert.</p> <p>Smooth PVC Concealing strip colour options & LRV's:</p> <p>Black LRV: 4.47 Polar Grey LRV: 42.73 Light Grey: 12.74 Yellow: 55.11</p> <div style="text-align: right;"> </div> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> Castellated Tread SRVs: PTV Dry - 82 PTV Wet - 54 </div>	
Specifications:	Material	Aluminium Alloy 6063 T6
	Tread Dimension	69mm
	Nosing Dimension	55mm
	Gauge	4.5mm ramping down to 0.5mm
	Lengths available	Cut to customer sizes up to 2500mm
	Finishes available & LRV's	Mill Aluminium Avg. LRV 71.65 Polished Aluminium Avg. LRV 75.55 Satin Aluminium Avg. LRV 65.40
	Drilling	Can be supplied pre-drilled and countersunk in the rear channel for concealed fixing and on-site retro fitting of cover strip. Drilled for size 8 screws. Fixings not supplied.
Application:	To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Installation guide available.	
Suitability:	Heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com