




**PRODUCT TECHNICAL DATA SHEET**

Revised: Oct 2021

<b>Catalogue Reference:</b>	<b>AN15R BA</b>	
<b>Uniclass2015:</b>	<b>Pr_35_90_31_74 RIGID STAIR NOSINGS</b>	
<b>General Description:</b>	<p><b>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL</b>  <b>Single Channel/Raked Front. Supplied with Castellated PVC Infill.</b></p> <p>Infill Colour Options &amp; LRV's:  <b>Black</b> LRV:4.25, <b>White</b> LRV:84.22, <b>Light Grey</b> LRV:12.33, <b>Flint</b> LRV:11.27, <b>Granite</b> LRV:7.02, <b>Rustic</b> LRV:5.52, <b>Fawn</b> LRV:11.27, <b>Ivory</b> LRV:37.42, <b>Spruce</b> LRV:6.38, <b>Jade</b> LRV:7.33, <b>Regency</b> LRV:5.16, <b>Mid Blue</b> LRV:6.53, <b>Nimbus</b> LRV:4.77, <b>Peat</b> LRV:5.88, <b>Yellow</b> LRV:54.91, <b>Poppy</b> LRV:10.01, <b>Claret</b> LRV:5.83, <b>Porth Stone</b> LRV:52.91, <b>Polar Grey</b> LRV:42.53</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;">             Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76         </div>	
<b>Specifications:</b>	Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound
	Tread Dimension	63.5mm
	Nosing Dimension	30mm
	Gauge	4mm ramping down to 0.5mm
	Lengths available	Cut to customer sizes up to 2500mm
	Finish & LRV	Black Anodised Avg. 4.80
	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill.  Drilled for size 8 screws. Fixings not supplied.
<b>Application:</b>	To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Installation guide available.	
<b>Suitability:</b>	For stairs with low to medium foot traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.	
<b>Additional Information:</b>	Also available with ATI49.5 tread insert for an all-aluminium installation and Olympic Grip carborundum infill for exterior/wet applications.	



Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

**Manufacturers Of The Finest Specialist Flooring Accessories**  
**www.thecatweb.com**