



PRODUCT TECHNICAL DATA SHEET

Revised: October 2021

Catalogue Reference:

ATI 62

Uniclass2015:

Pr_35_90_31_84 STAIR TRIMS

General Description:

ALUMINIUM STAIR INSERT WITH SLIP RESISTANT INFILL
Single Channel. Supplied with Olympic Grip carborundum Infill.

Infill Colour Options & LRV's:

Olympic Black LRV: 4.85



Olympic Grip Infill SRVs: PTV Dry - 92 PTV Wet - 86

Specifications:

Material	Aluminium Alloy 6063 T6
Tread Dimension	62mm
Nosing Dimension	n/a
Gauge	5mm
Lengths available	Cut to customer sizes up to 2750mm
Finishes available	Mill Aluminium '5j [" " @ J ' + % " *)
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill. Drilled for size 8 screws. Fixings not supplied.

Application:

For rebating into stone and wooden steps or with ceramic tiles, to provide a visual aid and some slip resistance. Installation guide available.

Suitability:

Very heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com