



PRODUCT TECHNICAL DATA SHEET

Revised: Oct 2021

Catalogue Reference:	BTI 25
Uniclass2015:	Pr_35_90_31_84 STAIR TRIMS
General Description:	<p>BRASS STAIR INSERT WITH RIBBED TREAD</p> <div style="text-align: center;"> </div> <div style="border: 1px solid black; padding: 5px; margin-top: 10px; text-align: center;"> SRVs: PTV Dry - 73 PTV Wet - 45 </div>

Specifications:	Material	Solid Brass Grade H/H CZ108 BS EN 12164:2016
	Tread Dimension	25mm
	Nosing Dimension	n/a
	Gauge	4.6mm
	Lengths available	Cut to customer sizes up to 2750mm
	Finishes available & Associated Light Reflective Values or LRV's	Polished Brass Avg. LRV 71.45 Satin Brass Avg. LRV 59.55 Antique Brass Avg. LRV 29.55 Antique Bronze Avg. LRV 9.15 Antique Brass and Antique Bronze finishes are a chemically applied process and are hand finished with a variance from batch to batch. They are not foot-traffic resistant and are designed to create an aged, unpolished effect.
	Fixing	Adhesive. *We recommend Stycco Flex rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use. Can be supplied drilled on request.
Application:	For rebating into stone and wooden steps or between ceramic tiles, to provide a visual aid and some slip resistance. Can be used in combination with stair nosings of equivalent thickness to create extended step going cover. Installation guide available.	
Suitability:	Heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com