



## PRODUCT TECHNICAL DATA SHEET

Revised: Oct 2021

<b>Catalogue Reference:</b>	<b>AN59R SL BA</b>															
<b>Uniclass2015:</b>	<b>Pr_35_90_31_74 RIGID STAIR NOSINGS</b>															
<b>General Description:</b>	<p><b>SLIMLINE ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL</b>  <b>Single Channel/Raked Front. Supplied with Smooth Textured PVC Infill.</b></p> <p>Tread Insert Finishes &amp; LRV's:</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 30%;">Black</td> <td>LRV 4.47</td> </tr> <tr> <td>Light Grey</td> <td>LRV 12.74</td> </tr> <tr> <td>Porth Stone</td> <td>LRV 53.11</td> </tr> <tr> <td>Polar Grey</td> <td>LRV 42.73</td> </tr> </table> <div style="text-align: right; margin-top: 10px;"> </div> <div style="border: 1px solid black; padding: 5px; margin-top: 10px; text-align: center;">             Smooth Textured Infill SRVs: PTV Dry - 65 PTV Wet - 56         </div>		Black	LRV 4.47	Light Grey	LRV 12.74	Porth Stone	LRV 53.11	Polar Grey	LRV 42.73						
Black	LRV 4.47															
Light Grey	LRV 12.74															
Porth Stone	LRV 53.11															
Polar Grey	LRV 42.73															
<b>Specifications:</b>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Materials</td> <td>Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound</td> </tr> <tr> <td>Tread Dimension</td> <td>59mm</td> </tr> <tr> <td>Nosing Dimension</td> <td>30mm</td> </tr> <tr> <td>Gauge</td> <td>2.5mm</td> </tr> <tr> <td>Lengths available</td> <td>Cut to customer sizes up to 2700mm</td> </tr> <tr> <td>Finish &amp; LRV</td> <td>Black Anodised Avg. LRV 4.80</td> </tr> <tr> <td>Drilling</td> <td>Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill.  Drilled for size 6 screws. Fixings not supplied.</td> </tr> </table>	Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound	Tread Dimension	59mm	Nosing Dimension	30mm	Gauge	2.5mm	Lengths available	Cut to customer sizes up to 2700mm	Finish & LRV	Black Anodised Avg. LRV 4.80	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill.  Drilled for size 6 screws. Fixings not supplied.	
Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound															
Tread Dimension	59mm															
Nosing Dimension	30mm															
Gauge	2.5mm															
Lengths available	Cut to customer sizes up to 2700mm															
Finish & LRV	Black Anodised Avg. LRV 4.80															
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill.  Drilled for size 6 screws. Fixings not supplied.															
<b>Application:</b>	For abutting to LVT and Vinyl to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Installation guide available.															
<b>Suitability:</b>	For stair with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.															
<b>Additional Information:</b>	Also available with AT149.5 Tread Insert for an all-aluminium installation and Olympic Grip carborundum infill for exterior/wet applications.															

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

**Manufacturers Of The Finest Specialist Flooring Accessories**  
**www.thecatweb.com**