



PRODUCT TECHNICAL DATA SHEET

Revised: Oct 2021

Catalogue Reference:

AN59R SL BA

Uniclass2015:


Pr_35_90_31_74 RIGID STAIR NOSINGS

General Description:

SLIMLINE ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL
Single Channel/Raked Front. Supplied with Castellated PVC Infill.

Infill Colour Options & LRV's:

Black LRV:4.25, **White** LRV:84.22, **Light Grey** LRV:12.33, **Flint** LRV:11.27, **Granite** LRV:7.02, **Rustic** LRV:5.52, **Fawn** LRV:11.27, **Ivory** LRV:37.42, **Spruce** LRV:6.38, **Jade** LRV:7.33, **Regency** LRV:5.16, **Mid Blue** LRV:6.53, **Nimbus** LRV:4.77, **Peat** LRV:5.88, **Yellow** LRV:54.91, **Poppy** LRV:10.01, **Claret** LRV:5.83, **Porth Stone** LRV:52.91, **Polar Grey** LRV:42.53



Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76

Specifications:

Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound
Tread Dimension	59mm
Nosing Dimension	30mm
Gauge	2.5mm
Lengths available	Cut to customer sizes up to 2700mm
Finish & LRV	Black Anodised Avg. 4.80
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill. Drilled for size 6 screws. Fixings not supplied.

Application:

For abutting to LVT and Vinyl to finish the nose edge of stairs.
Can be rebated to sit flush in wooden steps.
Installation guide available.

Suitability:

For stair with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.

Additional Information:

Also available with AT149.5 Tread Insert for an all-aluminium installation and Olympic Grip carborundum infill for exterior/wet applications.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com