

PRODUCT TECHNICAL DATA SHEET

Catalogue Reference:

BN71SLR

Uniclass2015:

Pr_35_90_31_74 **RIGID STAIR NOSINGS**

General Description:

BRASS STAIR NOSING WITH RAMPED BACK EDGE AND SLIP RESISTANT BRASS INFILL Single Channel/Square Front. Supplied with BTI49.5 Tread Insert

Revised: Oct 2021

Tread Insert finishes & LRV's:

Polished Brass Avg. LRV 71.45 Satin Brass Avg. LRV 59.55 Antique Brass Avg. LRV 29.55 Antique Bronze Avg. LRV 9.15

Finishes can be supplied to match or to contrast with base profile, as preferred.

Castellated Infill SRVs: PTV Dry - 82 PTV Wet - 54

Specifications:

Material	Solid Brass Grade H/H CZ108 BS EN 12164:2016
Tread Dimension	71mm
Nosing Dimension	30mm
Gauge	3.5mm ramping down to 0.5mm
Lengths available	Cut to customer sizes up to 3200mm
Channel Finishes available & Associated Light Reflective Values or LRV's	Polished Brass Avg. LRV 71.45 Satin Brass Avg. LRV 59.55 Antique Brass Avg. LRV 29.55 Antique Bronze Avg. LRV 9.15 Antique Brass and Antique Bronze finishes are a chemically applied process and are hand finished with a variance from batch to batch. They are not foot-traffic resistant and are designed to create an aged, unpolished effect.
Drilling	Can be supplied undrilled or pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the tread insert to cover the screw heads. Drilled for size 8 screws. Fixings not supplied.

Application:

To finish to nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino.

Suitability:

Very heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Additional Information:

Also available with Castellated/Smooth Textured PVC infill and Olympic Grip carborundum infill for added slip resistance.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com

website: www.thecatweb.com