



PRODUCT TECHNICAL DATA SHEET

Revised: October 2021

Catalogue Reference:	AN81									
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS									
General Description:	<p>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL Single Channel/Round Front. Supplied with Smooth Textured PVC Infill</p> <p>Tread Insert Finishes & LRV's:</p> <table> <tr> <td>Black</td> <td>LRV 4.47</td> </tr> <tr> <td>Light Grey</td> <td>LRV 12.74</td> </tr> <tr> <td>Porth Stone</td> <td>LRV 53.11</td> </tr> <tr> <td>Polar Grey</td> <td>LRV 42.73</td> </tr> </table> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;"> Smooth Textured Infill SRVs: PTV Dry - 65 PTV Wet - 56 </div> <div style="text-align: right; margin-top: 10px;"> </div>		Black	LRV 4.47	Light Grey	LRV 12.74	Porth Stone	LRV 53.11	Polar Grey	LRV 42.73
Black	LRV 4.47									
Light Grey	LRV 12.74									
Porth Stone	LRV 53.11									
Polar Grey	LRV 42.73									
Specifications:	Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound								
	Tread Dimension	68mm								
	Nosing Dimension	40mm								
	Gauge	5mm								
	Lengths available	Cut to customer sizes up to 3200mm								
	Finishes & LRV's	Mill Aluminium Avg. LRV 71.65 Polished Aluminium Avg. LRV 75.55 Satin Aluminium Avg. LRV 65.40								
	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads. Drilled for size 8 screws. Fixings not supplied.								
Application:	For abutting to carpet and carpet tiles to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Compatible with profiles ANE Nap Detail, ANRE25 Ramp Detail and ANEXT extension tread. Installation guide available.									
Suitability:	Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.									
Additional Information:	Also available with ATI49.5 tread insert for an all-aluminium installation and Olympic Grip carborundum infill for exterior/wet applications.									

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com