



**PRODUCT TECHNICAL DATA SHEET**

Revised: Oct 2021

<b>Catalogue Reference:</b>	<b>AN15R BA</b>	
<b>Uniclass2015:</b>	<b>Pr_35_90_31_74 RIGID STAIR NOSINGS</b>	
<b>General Description:</b>	<p><b>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT INFILL</b>  <b>Single Channel/Raked Front. Supplied with Olympic Grip Infill.</b></p> <p>Infill Colour Options &amp; LRV's:  <b>Olympic Black</b> LRV: 4.85</p> <div style="text-align: right;"> </div> <div style="border: 1px solid black; padding: 5px; margin-top: 10px; width: fit-content;"> <p>Olympic Grip Infill SRVs: PTV Dry - 92 PTV Wet - 86</p> </div>	
<b>Specifications:</b>	Material	Aluminium Alloy 6063 T6
	Tread Dimension	63.5mm
	Nosing Dimension	30mm
	Gauge	4mm ramping down to 0.5mm
	Lengths available	Cut to customer sizes up to 2500mm
	Finishes & LRV's	Black Anodised Avg. LRV 4.80
	Drilling	<p>Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill.</p> <p>Drilled for size 8 screws.            Fixings not supplied.</p>
<b>Application:</b>	<p>To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino.            Installation guide available.</p>	
<b>Suitability:</b>	<p>For stairs with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.</p>	
<b>Additional Information:</b>	<p>Also available with AT149.5 tread insert for an all-aluminium installation and Castellated/Smooth Textured PVC infill for interior applications.</p>	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

**Manufacturers Of The Finest Specialist Flooring Accessories**  
**www.thecatweb.com**