



PRODUCT TECHNICAL DATA SHEET

Revised: Oct 2021

Catalogue Reference:

BN55

Uniclass2015:


Pr_35_90_31_74 RIGID STAIR NOSINGS

General Description:

BRASS STAIR NOSING WITH SLIP RESISTANT PVC INFILL
Single Channel/Square Front. Supplied with Smooth Textured PVC Infill.

Tread Insert Finishes & LRV's:

Black	LRV 4.47
Light Grey	LRV 12.74
Polar Grey	LRV 42.73
Porth Stone	LRV 53.11



Smooth Textured Infill SRVs: PTV Dry - 65 PTV Wet - 56
--

Specifications:

Materials	Profile: Solid Brass Grade H/H CZ108 BS EN12164:2016 Infill: PVC Compound								
Tread Dimension	60mm								
Nosing Dimension	55mm								
Gauge	5mm								
Lengths available	Cut to customer sizes up to 3200mm								
Channel Finishes available & Associated Light Reflective Values or LRV's	<table border="0"> <tr> <td>Polished Brass</td> <td>Avg. LRV 71.45</td> </tr> <tr> <td>Satin Brass</td> <td>Avg. LRV 59.55</td> </tr> <tr> <td>Antique Brass</td> <td>Avg. LRV 29.55</td> </tr> <tr> <td>Antique Bronze</td> <td>Avg. LRV 9.15</td> </tr> </table> <p>Antique Brass and Antique Bronze finishes are a chemically applied process and are hand finished with a variance from batch to batch. They are not foot-traffic resistant and are designed to create an aged, unpolished effect.</p>	Polished Brass	Avg. LRV 71.45	Satin Brass	Avg. LRV 59.55	Antique Brass	Avg. LRV 29.55	Antique Bronze	Avg. LRV 9.15
Polished Brass	Avg. LRV 71.45								
Satin Brass	Avg. LRV 59.55								
Antique Brass	Avg. LRV 29.55								
Antique Bronze	Avg. LRV 9.15								
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads. Drilled for size 8 screws. Fixings not supplied.								

Application:

To butt to flooring or installed with BNE Nap Detail for carpet installations. Can be rebated to sit flush in wooden steps. Installation guide available.

Suitability:

Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Additional Information:

Also available with BT149.5 Tread Insert for an all-brass installation and Olympic Grip carborundum infill for added slip resistance.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com