



Part of the COBA Group

Revised: September 2023

MAINTENANCE GUIDE

Product Range:

ALUMINIUM STAIR NOSING PROFILES WITH PVC INFILL

Materials

Stair Nosing Profile: Aluminium Alloy 6063 T6
Infill: PVC Compound

General:

Immediately after installation and the removal of protective tape, the stair nosing profile should be wiped with a dry, soft cloth to remove any handling marks and fingerprints.

These aluminium stair nosings are produced with a highly polished, satin, or mill finish. The installed profile should be swept clean on a daily basis to avoid build up of dust and dirt which may make it more difficult to maintain its appearance and adversely affect performance.

Polished Finish:

Polished aluminium profiles require polishing with a suitable metal polish and a soft cloth in order to maintain their appearance. Make sure that all traces of polish are removed during polishing.

Do not allow polish build up on the tread section as this may affect the slip resistance performance.

Satin Finish:

Wipe clean with a mild detergent, diluted with water, on a damp, not wet, cloth. To remove scuffs and small scratches, a green or red Scotch pad can be used, rubbing along the grain of the existing finish.

Mill Finish:

Wipe clean with a mild detergent, diluted with water, on a damp, not wet, cloth. To remove light scuff marks, use a fine grade wire wool.

PVC Infill:

Wipe clean with a mild detergent, diluted with water, on a damp, not wet, cloth

Important:

Ensure that all surfaces are wiped dry after cleaning before opening the staircase to pedestrian traffic.

Care must be taken to protect surrounding floor finishes during maintenance.

Tip:

A small piece of velvet pile carpet, used upside down, will help clean to the bottom of castellated infill features.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com