

PRODUCT TECHNICAL DATA SHEET

Catalogue Reference:	ANT60/55/12.5 Pr_35_90_31_74 RIGID STAIR NOSINGS ALUMINIUM STAIR NOSING WITH SLIP RESISTANT INFILL Single Channel/Square Front. Supplied with Olympic Grip Carborundum Infill.	
Uniclass2015:		
General Description:		
	Infill Colour: Black	
Specifications:	Material	Aluminium Alloy 6063 T6
	Tread Dimension	60mm
	Nosing Dimension	55mm
	Gauge	12.5mm
	Lengths available	Cut to customer sizes up to 2750mm
·	Finishes available	Mill Aluminium, Satin Aluminium
	Drilling	Can be supplied pre-drilled and countersunk in the rear tail plate. Fixings are concealed by the adjoining floor covering.
		Drilled for size 8 screws. Fixings not supplied.
Application:	For use with thicker floor coverings such as ceramics, stone and timber to finish the nose edge of stairs. Installation guide available.	
Suitability:	Heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories www.thecatweb.com