

PRODUCT TECHNICAL DATA SHEET

Revised: July 2022

Catalogue Reference:

BN15


Uniclass2015:

Pr_35_90_31_74 **RIGID STAIR NOSINGS**

General Description:

BRASS STAIR NOSING WITH RAMPED BACK EDGE AND SLIP RESISTANT PVC INFILL Single Channel/Square Front. Supplied with Smooth Textured PVC Infill.

Infill colour options: Black, Light Grey, Porth Stone, Polar Grey.



Smooth Textured Infill SRVs: PTV Dry - 65 PTV Wet - 56

Specifications:

Materials	Profile: Solid Brass Grade H/H CZ108 BS EN12164:2016 Infill: PVC Compound
Tread Dimension	60mm
Nosing Dimension	30mm
Gauge	3.5mm ramping down to 0.5mm
Lengths available	Cut to customer sizes up to 3200mm
Finishes available	Polished Brass, Satin Brass, Antique Brass, Antique Bronze. Antique Brass and Antique Bronze finishes are a chemically applied process and are hand finished with a variance from batch to batch. They are not foot-traffic resistant and are designed to create an aged, unpolished effect.
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads. Drilled for size 6 screws. Fixings not supplied.

Application:

To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino.

Suitability:

Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Additional Information:

Also available with BTI49.5 Tread Insert for an all-brass installation and Olympic Grip carborundum infill for added slip resistance.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories www.thecatweb.com