

PRODUCT TECHNICAL DATA SHEET

Catalogue Reference:	AN15/55 DC	
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS DESIGNER COLLECTION ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL Single Channel/Square Front. Supplied with Castellated PVC Infill colour options: Black, White, Light Grey, Flint, Granite, Rustic, Fawn, Ivory, Spruce, Jade, Regency, Mid Blue, Nimbus, Peat, Yellow, Poppy, Claret, Porth Stone, Polar Grey. Store Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76	
General Description:		
Specifications:	Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound
	Tread Dimension	66mm
	Nosing Dimension	55mm
	Gauge	4mm ramping down to 0.5mm
	Lengths available	Cut to customer sizes up to 2750mm
	Finishes available	Bronze, Light Bronze DESIGNER COLLECTION
	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on- site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads. Drilled for size 6 screws. Fixings not supplied.
Application:	To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Installation guide available.	
Suitability:	Medium to heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public building, as well as for quality domestic installations.	
Additional Information:	Also available with Smooth Textured PVC insert, ATI49.5 tread insert for an all- aluminium installation and Smooth Textured PVC infill for interior installation.	
Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.		

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories www.thecatweb.com