

PRODUCT TECHNICAL DATA SHEET

Revised: June 2022

Catalogue Reference:

AN15/55

Uniclass2015:


Pr_35_90_31_74 RIGID STAIR NOSINGS

General Description:

ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL Single Channel/Square Front. Supplied with Castellated PVC Infill.

Infill colour options:
Black, White, Light Grey, Flint,
Granite, Rustic, Fawn, Ivory, Spruce,
Jade, Regency, Mid Blue, Nimbus,
Peat, Yellow, Poppy, Claret,
Porth Stone, Polar Grey.

Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76



Specifications:

Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound
Tread Dimension	66mm
Nosing Dimension	55mm
Gauge	4mm ramping down to 0.5mm
Lengths available	Cut to customer sizes up to 3200mm
Finishes available	Mill Aluminium, Satin Aluminium, Polished Aluminium.
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads. Drilled for size 8 screws. Fixings not supplied.

Application:

To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Installation guide available.

Suitability:

Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Additional Information:

Also available with Smooth Textured PVC insert, ATI49.5 tread insert for an all-aluminium installation and Olympic Grip carborundum infill for exterior/wet applications.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories www.thecatweb.com