




Part of the COBA Group

PRODUCT TECHNICAL DATA SHEET

Revised: June 2022

Catalogue Reference:	AN59/55 SL
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS
General Description:	<p>SLIMLINE ALUMINIUM STAIR NOSING WITH SLIP RESISTANT INFILL Single Channel/Square Front. Supplied with Olympic Grip Infill.</p> <p>Infill colour: Black</p>  <p>Olympic Grip Infill SRVs: PTV Dry - 92 PTV Wet - 86</p>

Specifications:	Material	Aluminium Alloy 6063 T6
	Tread Dimension	59mm
	Nosing Dimension	55mm
	Gauge	2.5mm
	Lengths available	Cut to customer sizes up to 3200mm
	Finishes available	Mill Aluminium, Satin Aluminium, Polished Aluminium.
	Drilling	<p>Can be supplied undrilled or pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill.</p> <p>Drilled for size 6 screws. Fixings not supplied.</p>
Application:	<p>For abutting to LVT and Vinyl to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Installation guide available.</p>	
Suitability:	<p>Very heavy interior foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.</p>	
Additional Information:	<p>Also available with ATI49.5 Tread Insert for an all-aluminium installation and Castellated/Smooth Textured PVC infill for interior applications.</p>	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com