



Part of the COBA Group

Revised: September 2023

## MAINTENANCE GUIDE

**Product Range:**

**STAINLESS STEEL STAIR NOSING PROFILES WITH PVC INFILL**

**Materials**

Stair Nosing Profile: Grade 304L Stainless Steel  
Infill: PVC Compound

**General:**

Immediately after installation and the removal of protective tape, the stair nosing profile should be wiped with a dry, soft cloth to remove any handling marks and fingerprints.

These stainless steel stair nosings are produced with a bright or brushed finish. The installed profile should be swept clean on a daily basis to avoid build up of dust and dirt which may make it more difficult to maintain its appearance and adversely affect performance.

**Stair Nosing Profile:**

Stainless steel profiles generally need little maintenance but heavy soiling can be cleaned using soap, ammonial or detergent and warm water. Sponge the soiled area with the solution, then rinse with clean water and dry. Goddards Stainless Steel Care may be used for stubborn stains. Always follow the manufacturer's instructions for use.

**PVC Infill:**

Wipe clean with a mild detergent, diluted with water, on a damp, not wet, cloth

**Important:**

**Ensure that all surfaces are wiped dry after cleaning before opening the staircase to pedestrian traffic.**

**Care must be taken to protect surrounding floor finishes during maintenance.**

**Tip:**

A small piece of velvet pile carpet, used upside down, will help clean to the bottom of castellated infill features.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: [sales@cat-accs.com](mailto:sales@cat-accs.com)

website: [www.thecatweb.com](http://www.thecatweb.com)

**Manufacturers Of The Finest Specialist Flooring Accessories**  
**[www.thecatweb.com](http://www.thecatweb.com)**