

PRODUCT TECHNICAL DATA SHEET

Catalogue Reference:	5: Pr_35_90_31_74 RIGID STAIR NOSINGS scription: ALUMINIUM STAIR NOSING WITH SLIP RESISTANT TREAD INSERT Single Channel/Raked Front. Supplied with ATI49.5 Tread Insert.	
Uniclass2015:		
General Description:		
	Tread Insert Finishes: Mill Aluminium, Polished Aluminium Satin Aluminium, Anodised Black. Finishes can be supplied to match or to contrast with the base profile, as preferred Castellated Infill SRVs: PTV Dry -	50.5 55 d.
Specifications:	Material	Aluminium Alloy 6063 T6
	Tread Dimension	66mm
	Nosing Dimension	55mm
	Gauge	4mm ramping down to 0.5mm
	Lengths available	Cut to customer sizes up to 2500mm
	Finishes available	Black Anodised
	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the tread insert to cover the screw heads. Drilled for size 6 screws. Fixings not supplied.
Application:	To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Installation guide available.	
	For stairs with low to medium foot traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.	
Additional Information:	Also available with Castellated/Smooth Textured PVC Infill for interior applications.	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories www.thecatweb.com