

## PRODUCT TECHNICAL DATA SHEET

Catalogue Reference:	AN15/55R	
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS	
General Description:	ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL Single Channel/Raked Front. Supplied with Castellated PVC Infill.	
	Infill colour options: Black, White, Light Grey, Flint, Granite, Rustic, Fawn, Ivory, Spruce, Jade, Regency, Mid Blue, Nimbus, Peat, Yellow, Poppy, Claret, Porth Stone, Polar Grey. Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76	
Specifications:	Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound
	Tread Dimension	66mm
	Nosing Dimension	55mm
	Gauge	4mm ramping down to 0.5mm
	Lengths available	Cut to customer sizes up to 2500mm
	Finishes available	Mill Aluminium, Satin Aluminium
	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads.
		Drilled for size 6 screws. Fixings not supplied.
Application:	To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Installation guide available.	
Suitability:	Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.	
Additional Information:	Also available with ATI49.5 tread insert for an all-aluminium installation and Olympic Grip carborundum infill for exterior/wet applications.	
Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.		
C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.		
T: +44 (0) 1582 561500 F: +44 (0) 1582 561900		
email: sales@cat-accs.com website: www.thecatweb.com		

## Manufacturers Of The Finest Specialist Flooring Accessories www.thecatweb.com