




Part of the COBA Group

# PRODUCT TECHNICAL DATA SHEET

Revised: June 2022

<b>Catalogue Reference:</b>	<b>AN15/55R BA with Smooth Textured Insert</b>
<b>Uniclass2015:</b>	<b>Pr_35_90_31_74 RIGID STAIR NOSINGS</b>
<b>General Description:</b>	<p><b>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL</b>  <b>Single Channel/Raked Front. Supplied with Smooth Textured PVC Infill.</b></p> <p>Infill colour options:          Black, Light Grey, Porth Stone, Polar Grey.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;">             Smooth Textured Infill SRVs: PTV Dry - 65 PTV Wet - 56         </div> 

<b>Specifications:</b>	Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound
	Tread Dimension	66mm
	Nosing Dimension	55mm
	Gauge	3.5mm ramping down to 0.5mm
	Lengths available	Cut to customer sizes up to 2500mm
	Finishes available	Black Anodised.
	Drilling	<p>Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill, or through the infill with smooth pips supplied to cover the screw heads.</p> <p>Drilled for size 6 screws.              Fixings not supplied.</p>
<b>Application:</b>	To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Installation guide available.	
<b>Suitability:</b>	For stairs with low to medium foot traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.	
<b>Additional Information:</b>	Also available with AT149.5 tread insert for an all-aluminium installation.	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

**Manufacturers Of The Finest Specialist Flooring Accessories**  
**www.thecatweb.com**