



Part of the COBA Group

Revised: September 2023

MAINTENANCE GUIDE

Product Range:

AR110/10 – Aluminium Wide Ramp

Material

Aluminium Alloy 6063 T6 – Mill Finish

General:

The installed profile should be swept clean on a daily basis to avoid build up of dust and dirt which may make it more difficult to maintain its appearance. Immediately after installation and the removal of protective tape, the flooring profile should be wiped with a dry, soft cloth to remove any handling marks and fingerprints.

Cleaning:

The mill surface finish can be cleaned using soap and warm water. Wipe clean with a mild detergent, diluted with water, on a damp, not wet, cloth. To remove light scuffs marks, use a fine grade wire wool. Prolonged exposure to damp environments, acids or strong alkali solutions may lead to corrosion of the metal.

Important:

Ensure that all surfaces are wiped dry after cleaning before allowing pedestrian access.
Care must be taken to protect surrounding floor finishes during maintenance.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com