



Part of the COBA Group

PRODUCT TECHNICAL DATA SHEET

Revised: June 2022

Catalogue Reference:

AN59/55R SL

Uniclass2015:


Pr_35_90_31_74 RIGID STAIR NOSINGS

General Description:

SLIMLINE ALUMINIUM STAIR NOSING WITH SLIP RESISTANT TREAD INSERT
Single Channel/Raked Front. Supplied with ATI49.5 Tread Insert.

Tread Insert Finishes:
 Mill Aluminium, Polished Aluminium,
 Satin Aluminium, Anodised Black.

Finishes can be supplied to match or to
 contrast with the base profile, as preferred.



Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76

Specifications:

Material	Aluminium Alloy 6063 T6
Tread Dimension	59mm
Nosing Dimension	55mm
Gauge	2.5mm
Lengths available	Cut to customer sizes up to 2500mm
Finishes available	Mill Aluminium, Satin Aluminium, Polished Aluminium.
Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the tread insert to cover the screw heads. Drilled for size 6 screws. Fixings not supplied.

Application:

For abutting to LVT and Vinyl to finish the nose edge of stairs.
 Can be rebated to sit flush in wooden steps.
 Installation guide available.

Suitability:

Very heavy interior foot traffic situations such as in hotels, pubs, clubs, cafes, shops,
 schools, commercial offices and apartment buildings.

Additional Information:

Also available with Olympic Grip carborundum infill for exterior/wet applications
 and Castellated/Smooth Textured PVC Infill for interior applications.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com