

PRODUCT TECHNICAL DATA SHEET

Revised: June 2022

Catalogue Reference:

AN82

Uniclass2015:

Pr_35_90_31_74 RIGID STAIR NOSINGS

General Description:

ALUMINIUM STAIR NOSING WITH SLIP RESISTANT INFILL Double Channel/Round Front. Supplied with Olympic Grip Infill.

Infill colour: Black



Olympic Grip Infill SRVs: PTV Dry - 92 PTV Wet - 86

Specifications:

Material	Aluminium Alloy 6063 T6
Tread Dimension	98mm
Nosing Dimension	40mm
Gauge	5mm
Lengths available	Cut to customer sizes up to 3200mm
Finishes available	Mill Aluminium, Satin Aluminium, Polished Aluminium.
Drilling	Can be supplied undrilled or pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill. Drilled for size 8 screws. Fixings not supplied.

Application:

For abutting to carpet and carpet tiles to finish the nose edge of stairs.

Can be rebated to sit flush in wooden steps.

Compatible with profiles ANE Nap Detail, ANRE25 Ramp Detail and

ANEXT extension tread. Installation guide available.

Suitability:

Heavy foot traffic and exterior/wet situations such as in hotels, pubs, clubs, cafes,

shops, schools, commercial offices and apartment buildings.

Additional Information:

Also available with ATI37.25 tread insert for an all-aluminium installation, and Castellated/Smooth Textured PVC infill for interior applications.

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories www.thecatweb.com