

Revised: September 2023

MAINTENANCE GUIDE

Product Range: Base Material Aluminium Alloy 6063 T6 **General:** The installed profile should be swept clean on a daily basis to avoid build up of dust and dirt which may make it more difficult to maintain its appearance. Immediately after installation and the removal of protective tape, the flooring profile should be wiped with a dry, soft cloth to remove any handling marks and fingerprints. DHC profiles are a available in the following finishes: Satin Bright, Bronze, Light Bronze, Pewter, Brushed Stainless, Onyx, Piano Black. DHC finishes are an applied process and are not heavy foot-traffic resistant.

Cleaning: DHC finishes can be cleaned using soap and warm water.

DHC (Designer Home Collection) Profiles

Sponge the soiled area with the solution, then rinse with clean water and dry. Prolonged exposure to damp environments, acids or strong alkali solutions may

lead to corrosion of the metal.

Ensure that all surfaces are wiped dry after cleaning before allowing pedestrian Important: access.

Care must be taken to protect surrounding floor finishes during maintenance.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com