



Part of the COBA Group

PRODUCT TECHNICAL DATA SHEET

Revised: June 2022

Catalogue Reference:	ANT60/55/12.5	
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS	
General Description:	<p>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT TREAD INSERT Single Channel/Square Front. Supplied with ATI49.5 Tread Insert.</p> <p>Tread Insert Finishes: Mill Aluminium, Polished Aluminium, Satin Aluminium, Anodised Black.</p> <p>Finishes can be supplied to match or to contrast with the base profile, as preferred.</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;"> Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76 </div>	
Specifications:	Material	Aluminium Alloy 6063 T6
	Tread Dimension	60mm
	Nosing Dimension	55mm
	Gauge	12.5mm
	Lengths available	Cut to customer sizes up to 2750mm
	Finishes available	Mill Aluminium, Satin Aluminium
	Drilling	<p>Can be supplied pre-drilled and countersunk in the rear tail plate. Fixings are concealed by the adjoining floor covering.</p> <p>Drilled for size 8 screws. Fixings not supplied.</p>
Application:	<p>For use with thicker floor coverings such as ceramics, stone and timber to finish the nose edge of stairs. Installation guide available.</p>	
Suitability:	<p>Heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.</p>	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com